



ADB995

The ABD995 is the solution to ease installation of the operator positions that MEP offers. It **speeds up installation** by simplifying wiring the D-SUB 25 to the different peripherals installed around the console such as speaker boxes, handset, fist microphones, foot bar, voice logging and the ACU995 headset extension. The wiring between the ADB995 and the other MEP products are **standard issued cables** or can be ordered from MEP, negating the need for specialized cables for each project.

Key Features

Interfaces

- ✓ Console connector (DB25)
- ✓ ACU995 connection (DB25)
- ✓ 2x Speaker box connection (RJ45)
- ✓ Headset (RJ45)
- ✓ Handset connection (RJ45)
- ✓ Handset cradle connection (RJ12)
- ✓ Voice logging output (RJ45)
- ✓ External PTT (foot switch, 2-pin contact)
- ✓ Error line input (2-pin contact)
- ✓ Fist microphone (RJ45)

Supported consoles

- ✓ STP995
- ✓ SVP995
- ✓ TCP995
- ✓ TDP995

Other features

- Dimensions** 163 x 130 mm
- EMC** EN 55032, EN 55035
- Safety** EN 62368-1
- Temperature** -40°C till 70°C

Supported peripherals

- ✓ ACU995
- ✓ SBU995
- ✓ CRA995
- ✓ TBU995
- ✓ Handset
- ✓ Voice logging
- ✓ Footswitch
- ✓ Fist microphone
- ✓ Wireless headset
- ✓ Error line input