



STP995 (MIC) Console

The STP995 is a 5.7" touchscreen CWP. The CWP is equipped with a 560CD/m² VGA touch screen. The unit can be mounted in a standard 19" rack or by VESA 100 mounting holes. It can be delivered with a handset. The panel has two volume knobs, a touch PTT button a speaker, an internal microphone and two LEMO connectors for a handset and headset. At the rear, there is an extension connector to connect more audio modules. The STP995 is provided with two IP interfaces and redundant power input.

Key Features

Touch Interface

Screen Resolution	640 x 480
Screen size	5.7"
Viewing angle	135° (H&V)
Brightness	480 cd/m ²

- ✓ Resistive touch screen
- ✓ Configurable Avatar interface

Audio

- ✓ Internal Loudspeker
- ✓ Internal microphone or goose neck microphone
- ✓ Handset connection
- ✓ Headset connection
- ✓ 2 External loudspeaker connections
- ✓ External microphone connection
- ✓ 2 Internal volume controls
- ✓ 2 External connections for volume control
- ✓ Voicelogging connection
- ✓ All audio levels can be arranged

Connections

- ✓ 2 Ethernet connections
- ✓ E1 connection (with module)

Applications

- ✓ Switchless
- ✓ Switch in combination with TCS990
- ✓ ED137 compatible

Other features

- ✓ Realtime clock with battery
- ✓ Footswitch connection

Dimensions	245 x 129 x 50 mm
Power	12V
EMC	EN55032, EN55035
Safety	EN62368-1
Temperature	-10°C tot 50°C (fanless)