



SureVoice Panel7

The SureVoice Panel7 is the versatile **controller working position** (CWP) of the SureVoice VCS. The SureVoice Panel7 is a high-reliable complete CWP. It features **two 1000 Base-T Gigabit Ethernet jacks** with optional PoE to maintain a redundant connection to the network.

Key Features

Connections

- ✓ 2x 1000 Base-T Gigabit Ethernet
- ✓ 2x PoE++
- ✓ 1x Customer specific auxiliary port
- ✓ Optional USB type-C (3.1 gen 1) port

Power

- ✓ Power usage 30 W
- ✓ 15 – 50 VDC input (not needed when PoE is used)

Dimensions

Width	25 cm
Height	13,5 cm
Depth	9 cm

Mounting options

- ✓ VESA 100
- ✓ Free Table Stand
- ✓ In desk
- ✓ In 19" subrack

Interoperability

- ✓ ED-137

Audio

- ✓ 2x Digital connector for External audio
- ✓ Integrated speaker
- ✓ Integrated PTT button
- ✓ Optional integrated gooseneck microphone
- ✓ Optional integrated LEMO Headset socket

Display

- ✓ 7" Display
- ✓ 800 x 480
- ✓ Capacitive touch screen
- ✓ Brightness 1000 Cd/m²
- ✓ Viewing angle 85°

Applications

- ✓ VCS system in ATC
- ✓ VCS system in Maritime

Operating environment

Temperature	0 to 50 °C
Humidity	5 – 95% non-condensing

Regulations

EMC	EN 55032, EN 55035
Safety	EN 62368-1